

SDE 30

SIMAG

30 kg Self-contained Ice Machine

Complete range: SDE 18 - SDE 24 - SDE 30 - SDE 34 - SDE 40 - SDE 50 - SDE 64 - SDE 84 - SDE 100 - SDE 170 - SDE 220

Technical features

- Stainless steel bodywork - scotch brite
- Air or water cooled
- Vertical pump
- Main switch (ON/OFF)
- Built-in cleaning system
- Easily accessible components
- Low power and water consumption
- Optimum ratio between ice production and bin capacity
- Reduced dimensions
- Double defrosting system



Internal bin capacity




6 kg of ice

290 cubes

Type of ice

Hollow Cubes



Machine dimensions

Net size WxDxH	334 x 457 x 599 mm
Net weight	28 kg
Shipping size WxDxH	400 x 530 x 690 mm
Shipping weight	33 kg

Voltage

230/50/1 Standard version

220-240/60/1 Available on demand

Technology and Certifications



MILANO OFFICE
Sales Dept.
Tel. +39 02 93900215
e-mail: sales@simag.it
Service Dept.
Tel. +39 02 93960357
e-mail: service@simag.it

SIMAG FAR EAST
Singapore Office
Tel. ++65 6738 5393
e-mail: scotsman@scotsman.com.sg

www.simag.it

SIMAG

Complete range: SDE 18 - SDE 24 - SDE 30 - SDE 34 - SDE 40 - SDE 50 - SDE 64 - SDE 84 - SDE 100 - SDE 170 - SDE 220



	Minimum	Maximum
Air temperature	10°C	43°C
Water temperature	5°C	38°C
Water pressure	1 bar	5 bar
Electrical voltage	-10 %	+10 %

Model	Voltage	Daily production kg	Power input Watt (*)	Refrigerant		Fuse A	Consumptions (**)		
		10°C/10°C		Type	Charge kg		kWh/100kg	kWh/24h	Water l/h
SDE 30 A	230/50/1	30	380	R134a	0.210	10	n.a.	n.a.	4.2
SDE 30 W	230/50/1	28	220	R134a	0.170	10	n.a.	n.a.	20.0
SDE 30 A	220/60/1	30	380	R134a	0.210	10	n.a.	n.a.	4.2
SDE 30 W	220/60/1	28	220	R134a	0.170	10	n.a.	n.a.	20.0
(*) Power Input: at 43°C Ambient Temperature									
(**) Water Consumption: at 32°C Air and 21°C Water									